



**POLYURETHANE**  
MACHINERY CORPORATION

# PREMIER

IDEAL FOR HIGH OUTPUT  
RESIDENTIAL AND COMMERCIAL  
APPLICATIONS

**PREMIER** is the most  
technologically advanced  
proportioner in the PMC line-up

**PREMIER** puts you in  
complete control with intuitive  
design and remote capabilities

PMC RELIABILITY MEETS THE FUTURE OF  
PLURAL COMPONENT PROPORTIONERS

## KEY FEATURES:

- Up to **40 lbs per minute** Foam
- User management and traceability features
- **Touchscreen dashboard** - all controls at your fingertips
- Chemical management display insures that ratio, temperature and pressures are accurate
- Reporting software captures **data in real time** and can email daily reports
- Saves all historical data and alarms
- On-screen technical support
- System settings in English and Spanish
- **Remote access** from any web enabled device



MADE IN THE USA



[POLYMAC-USA.COM](http://POLYMAC-USA.COM)

**BUY THE BEST THE FIRST TIME.**

WORLDWIDE HEADQUARTERS  
One Komo Drive Lakewood, NJ 08701 USA  
P: (732) 415-4400 | E: [marketing@polymacusa.com](mailto:marketing@polymacusa.com)

### STANDARD FEATURES

**Remote access** proportioner from any web enabled device, without the need to download a specific app. Proportioner can be run remotely if desired.

**User management and traceability** features allow owners to create unique user ID's or a generic user for each function, i.e. operator, tech support, owner.

On-screen **technical support view** displays raw data to help diagnose issues.

**Chemical management display** ensures that ratio, temperature and pressures are accurate with user selectable setpoints for upper and lower limits.

**Reporting software** captures data in real time, and can be displayed on a graph for easy-to-see results or reports can be emailed directly from the machine.



### TECHNICAL DATA

MODEL	PREMIER
Output* .....	40 lbs/min (18.14 kg/min)
Max. Working Pressure.....	2,000 psi (138 bar)
Max. Hose Length.....	410 ft (121.9 m)
Heater Wattage .....	18,000 watts (Dual htr)
Hose Heating Power .....	120 volts
Max. Fluid Temp .....	190 °F (87.7 °C)
Weight (Empty Hydraulic Tank).....	670 lbs (304 kg)
Weight (Full Hydraulic Tank).....	844 lbs (383 kg)
Electrical @ 18KW Heaters.....	67 amps @ 3 x 230V
Dimensions (W x D x H).....	40in x 30in x 55in (102cm x 76cm x 140cm)

\*Output measured with mineral oil

### ORDERING INFORMATION

PART#.....	DESCRIPTION
<b>PREMIER</b>	
203011.....	PRMR,5HP,220V,3PH,RV,120T,18KW

### PMC LEGEND FOR MACHINE DESCRIPTIONS

**PH-2**.....Machine Series  
**3HP**.....Horsepower (3hp, 5hp, 7.5hp)  
**230V**.....Voltage (230v, 380v or 460v)

**1PH**.....Phase (Single or Three)  
**RV**.....Recirculation Valves  
**90T**.....Transformer Size (30V, 70V, 90V, or 120V)

**10KW** ... Heater Wattage  
**IM**..... Inlet Monitoring  
**PBC** ..... Pressure Balance Control

